

## Material Safety Data Sheet

May be used to comply with  
OSHA's Hazard Communication Standard,  
29 CFR 1910.1200. Standard must be  
consulted for specific requirements.

## U.S. Department of Labor

Occupational Safety and Health Administration  
Essentially similar to Non-Mandatory  
Approved O.S.H.A. Form  
OMB No. 1218-0072

### IDENTITY

**211-M Armor Plate with Moly-D® Industrial Multigrade Hydraulic Oil**

## SECTION I

**Primrose Oil Company, Inc.**  
11444 Denton Drive  
PO Box 29665  
Dallas, Texas 75229

**Emergency Only Telephone No. 800/633-8253**  
**Telephone Number for Information: 972-241-1100**  
**Date Prepared: February 1, 2009**

## SECTION II - Hazardous Ingredients Identity/Information

None

## SECTION III - Physical/Chemical Characteristics

Boiling Point	N/A.	Specific Gravity (H <sub>2</sub> O = 1)	0.9.
Vapor Pressure (mm Hg.)	N/A.	Melting Point	N/A.
Vapor Density (AIR = 1)	N/A.	Evaporation Rate (Butyl Acetate = 1)	N/A.

Solubility in Water: Insoluble

Appearance and Odor: Green colored liquid, mild petroleum odor.

## SECTION IV - Fire and Explosion Hazard Data

Flash Point (Method Used: 199°C (COC), min.	Flammable Limits: N/A.	LEL n.a.	UEL N/A.
---	------------------------	----------	-------------

Extinguishing Media: CO<sub>2</sub>, dry chemical, foam or water fog.

Special Fire Fighting Procedures: Wear self-contained breathing apparatus for fires in confined spaces.

Unusual Fire and Explosion Hazards: N/A.

