

SAFETY DATA SHEET

ProtectOLube 4000

Prepared to U.S. OSHA, CMA, ANSI, Canadian WHMIS Standards, Australian WorkSafe, Japanese Industrial Standard JIS Z 7250:2000, and European Directives

SECTION 1. PRODUCT IDENTIFICATION

1.1 PRODUCT NAME: **ProtectOLube 4000**
PRODUCT NUMBER: 400P
PRODUCT DESCRIPTION: Mixture
1.2 PRODUCT USE: Aerosol Lubricant
1.3 MANUFACTURER'S NAME: **Primrose Oil Company, Inc.**
ADDRESS: 11444 Denton Drive, P.O. 29665, Dallas, Texas 75229 USA
EMERGENCY PHONE: 1-800-633-8253 (For Emergencies Only)
BUSINESS PHONE: 1-972-241-1100 (For product information)
WEB SITE INFORMATION: www.primrose.com
DATE OF CURRENT REVISION: December 1, 2016
DATE OF LAST REVISION: July 19, 2016, September 16, 2025

SECTION 2. HAZARD IDENTIFICATION

EMERGENCY OVERVIEW: This product is an amber to orange aerosol with a mild petroleum odor.
Health Hazards: Repeated or prolonged contact with skin may cause burns or severe irritation. Contact with eyes can cause damage. Inhalation of vapors or mist can cause irritation, drowsiness or dizziness. May be harmful if swallowed.
Flammability Hazards: This product is a combustible liquid and vapor.
Reactivity Hazards: No data available.
Environmental Hazards: The environmental effects of this product have not been investigated, however release may cause long term adverse environmental effects.

2.1 GHS LABELING AND CLASSIFICATION:

This product does meet the definition of a hazardous substance or preparation as defined by 29 CFR 1910. 1200 and regulation (EU) No. 2015/830 and regulation (EC) No. 1272/2008.

Component(s) Contributing to Classification(s)

Severely Hydrotreated Light Naphthenic Petroleum Oil, Severely Hydrotreated Light Mineral Oil, Butanol

2.2 LABEL ELEMENTS

US DOT SYMBOLS



CANADA (WHMIS) SYMBOL(S)

Complies with WHMIS 2015

EUROPEAN and (GHS) Hazard Symbol(s)



Signal Word: **Danger!**

GHS Hazard Classification(s):

Flammable Aerosol Category 2
Acute Oral Toxicity Category 4 (Oral)
STOT SE Category 3 (Respiratory and Central Nervous Systems)
Skin Irritation Category 2
Eye Damage Category 1

Hazard Statement(s):

H223 Flammable aerosol
H302 Harmful if swallowed
H335 May cause respiratory irritation
H336 May cause drowsiness and dizziness
H315 Causes mild skin irritation
H318 Causes serious eye damage

Prevention Statement(s):

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P211 Do not spray on an open flame or other ignition source.
P251 Do not pierce or burn, even after use.
P261 Avoid breathing dust/fume/gas/mist/vapours/spray.
P271 Use only outdoors or in a well-ventilated area.
P264 Wash thoroughly after handling.
P270 Do not eat, drink or smoke when using this product.
P280 Wear protective gloves, eye protection/face protection.

SAFETY DATA SHEET

ProtectOLube 4000

Storage Statement(s):

P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.
P403+P233 Store in a well-ventilated place. Keep container tightly closed.
P405 Store locked up.

Disposal Statement(s):

P501: Dispose of contents/container in accordance with local/regional/national/international regulations

Response Statement(s):

P301+P312 IF SWALLOWED: Call a POISON CENTER/doctor if you feel unwell.
P330 Rinse mouth.
P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P312 Call a POISON CENTER/doctor if you feel unwell.
P332+P313: If skin irritation occurs: Get medical advice/attention.
P302+P352: IF ON SKIN: Wash with plenty of water.
P362+P364: Take off contaminated clothing and wash it before reuse.
P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P310 Immediately call a POISON CENTER/doctor.

2.3 OTHER HAZARDS:

None Applicable

SECTION 3. COMPOSITION AND INFORMATION ON INGREDIENTS

Hazardous Ingredients:	WT%	CAS #	EINECS #	Index #	Hazard Classification
Severely Hydrotreated Light Naphthenic Petroleum Oil	40 – 50%	64742-53-6	265-156-6	649-466-00-2	Not Classified per Note L
Severely Hydrotreated Light Mineral Oil	40 – 50%	64742-46-7	265-148-2	649-221-00-X	Not Classified per Note N
Butanol	5 – 15%	71-36-3	200-751-6	603-004-00-6	Flammable Liq 3, Acute Toxicity Cat 4 (Oral), Skin Irritation Cat 2, Eye Damage Cat 1, STOT SE 3 (Respiratory System and Central Nervous System)
Balance of other ingredients are non-hazardous or less than 1% in concentration (or 0.1% for carcinogens, reproductive toxins, or respiratory sensitizers). *Note L- less than 3 % DMSO extract as measured by IP 346. *Note N - applies only to certain complex oil-derived substances in Part 3.					

NOTE: ALL WHMIS required information is included in appropriate sections based on the ANSI Z400.1-2010 format. This product has been classified in accordance with the hazard criteria of the CPR and the SDS contains all the information required by the CPR, EU Directives and the Japanese Industrial Standard JIS Z 7250: 2000

SECTION 4. FIRST-AID MEASURES

4.1 DESCRIPTION OF FIRST AID MEASURES:

EYE CONTACT: If product enters the eyes, open eyes while under gentle running water for several minutes. Remove contact lenses if present and easy to do. Continue rinsing for at least 15 minutes. Seek medical attention.

SKIN CONTACT: Wash skin thoroughly after handling. Seek medical attention if irritation develops and persists. Remove contaminated clothing. Launder before re-use.

INHALATION: If breathing becomes difficult, remove victim to fresh air. If necessary, use artificial respiration to support vital functions. Seek medical attention.

INGESTION: If product is swallowed, call physician or poison control center for most current information. If professional advice is not available, do not induce vomiting. Never induce vomiting or give diluents (milk or water) to someone who is unconscious, having convulsions, or who cannot swallow. Seek medical advice. Take a copy of the label and/or SDS with the victim to the health professional.

MEDICAL CONDITIONS AGGRAVATED BY EXPOSURE: Pre-existing eye problems may be aggravated by prolonged contact.

4.2 SYMPTOMS AND EFFECTS, BOTH ACUTE AND DELAYED:

Prolonged contact may cause irritation of skin and respiratory system. May cause drowsiness and dizziness. Contact with the eyes may cause damage.

4.3 RECOMMENDATIONS TO PHYSICIANS:

Treat symptoms and eliminate overexposure.

SAFETY DATA SHEET

ProtectOLube 4000

SECTION 5. FIRE-FIGHTING MEASURES

5.1 FIRE EXTINGUISHING MATERIALS:

Use fire extinguishing methods below:

Water Spray: Yes Carbon Dioxide: Yes
Foam: Yes Dry Chemical: Yes
Halon: Yes Other: Any "C" Class

5.2 UNUSUAL FIRE AND EXPLOSION HAZARDS:

Above flash point, vapor air mixtures are explosive within flammable limits noted above. Vapor can flow along surfaces to distant ignition sources and flash back.


Explosion Sensitivity to Mechanical Impact: No

Explosion Sensitivity to Static Discharge: Yes

5.3 SPECIAL FIRE-FIGHTING PROCEDURES:

Incipient fire responders should wear eye protection. Structural firefighters must wear Self-Contained Breathing Apparatus and full protective equipment. Isolate materials not yet involved in the fire and protect personnel. Move containers from fire area if this can be done without risk; otherwise, cool with carefully applied water spray. If possible, prevent runoff water from entering storm drains, bodies of water, or other environmentally sensitive areas.

NFPA RATING SYSTEM



HMIS RATING SYSTEM

HAZARDOUS MATERIAL IDENTIFICATION SYSTEM			
HEALTH HAZARD (BLUE)			2
FLAMMABILITY HAZARD (RED)			2
PHYSICAL HAZARD (YELLOW)			0
PROTECTIVE EQUIPMENT			
EYES	RESPIRATORY	HANDS	BODY
	See Sect 8		See Sect 8
For Routine Industrial Use and Handling Applications			

Hazard Scale: 0 = Minimal 1 = Slight 2 = Moderate 3 = Serious 4 = Severe * = Chronic hazard

SECTION 6. ACCIDENTAL RELEASE MEASURES

6.1 PERSONAL PRECAUTIONS, PROTECTIVE EQUIPMENT AND EMERGENCY PROCEDURES:

Shut off all ignition sources. No flares, smoking or flames in hazard area. Avoid breathing dust. Provide adequate ventilation. Wear suitable protective clothing, gloves and eye/face protection. Evacuate personnel to safe areas.

6.2 ENVIRONMENTAL PRECAUTIONS:

Not applicable.

6.3 SPILL AND LEAK RESPONSE:

Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Prevent entry into sewers, water courses, basement or confined areas. Avoid dust generation. Do not dry sweep. Vacuum dust with equipment fitted with a HEPA filter and place in a closed, labeled waste container. Avoid creating dusty conditions and prevent wind dispersal. Dispose of via a licensed waste disposal contractor.

SECTION 7. HANDLING and STORAGE

7.1 PRECAUTIONS FOR SAFE HANDLING:

To prevent skin and eye contact under the foreseeable conditions of use, wear appropriate protective clothing and safety eyewear. When handling, do not eat, drink, or smoke. Wash thoroughly after handling. Handle in a well-ventilated work area.

SAFETY DATA SHEET

ProtectOLube 4000

7.2 STORAGE AND HANDLING PRACTICES:

Keep away from incompatible materials. Eliminate all ignition sources. Keep in a dry, well-ventilated area in closed containers. Protect containers from physical damage. Keep container tightly closed and sealed until ready for use. Store in accordance with local regulations.

7.3 SPECIFIC USES:

Various uses.

SECTION 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

8.1 EXPOSURE PARAMETERS:

Chemical Name	CAS#	ACGIH TWA	OSHA TWA
Severely Hydrotreated Light Naphthenic Petroleum Oil	64742-53-6	5 mg/m ³ Oil Mist	5 mg/m ³ Oil Mist
Severely Hydrotreated Light Mineral Oil	64742-46-7	5 mg/m ³ Oil Mist	5 mg/m ³ Oil Mist
Butanol	71-36-3	20 ppm	100 ppm

8.2 EXPOSURE CONTROLS:

VENTILATION AND ENGINEERING CONTROLS: Use with adequate ventilation to ensure exposure levels are maintained below the limits provided above.

The following information on appropriate Personal Protective Equipment is provided to assist employers in complying with OSHA regulations found in 29 CFR Subpart I (beginning at 1910.132) or equivalent standard of Canada, or standards of EU member states (including EN 149 for respiratory PPE, and EN 166 for face/eye protection), and those of Japan. Please reference applicable regulations and standards for relevant details.

RESPIRATORY PROTECTION: Not required for properly ventilated areas. Maintain airborne contaminant concentrations below guidelines listed above, if applicable. If necessary, use only respiratory protection authorized in the U.S. Federal OSHA Respiratory Protection Standard (29 CFR 1910.134), equivalent U.S. State standards, Canadian CSA Standard Z94.4-93, the European Standard EN149, or EU member states.

EYE PROTECTION: Safety glasses or goggles are required. If necessary, refer to U.S. OSHA 29 CFR 1910.133, Canadian Standards, and the European Standard EN166, Australian Standards, or relevant Japanese Standards.

HAND PROTECTION: Chemical resistant gloves are required to prevent skin contact. If necessary, refer to U.S. OSHA 29 CFR 1910.138, the European Standard DIN EN 374, the appropriate Standards of Canada, Australian Standards, or relevant Japanese Standards.

BODY PROTECTION: Use body protect appropriate to task being performed. If necessary, refer to appropriate Standards of Canada, or appropriate Standards of the EU, Australian Standards, or relevant Japanese Standards. If a hazard of injury to the feet exists due to falling objects, rolling objects, where objects may pierce the soles of the feet or where employee's feet may be exposed to electrical hazards, use foot protection, as described in U.S. OSHA 29 CFR 1910.136.

SECTION 9. PHYSICAL and CHEMICAL PROPERTIES

9.1 INFORMATION ON BASIC PHYSICAL AND CHEMICAL PROPERTIES:

APPEARANCE (Physical State) and COLOR: This product is an amber to orange aerosol.

ODOR: Mild petroleum odor

ODOR THRESHOLD: Mild

pH: Not Available

MELTING/FREEZING POINT: Not Available

BOILING POINT: 244°F

FLASH POINT: Combustible liquid and vapor >102°F

EVAPORATION RATE (n-BuAc=1): Not Applicable

FLAMMABILITY (SOLID, GAS): Not Applicable

UPPER/LOWER FLAMMABILITY OR EXPLOSION LIMITS: Not Available

VAPOR PRESSURE (mm Hg @ 20°C (68°F): Not Applicable

VAPOR DENSITY: >2.6

RELATIVE DENSITY: Not Available

SPECIFIC GRAVITY: 0.9

SOLUBILITY IN WATER: Partial

WEIGHT PER GALLON: Not Available

PARTITION COEFFICIENT (n-octanol/water): Not Available

SAFETY DATA SHEET

ProtectOLube 4000

AUTO-IGNITION TEMPERATURE: Not Available
DECOMPOSITION TEMPERATURE: Not Available
VISCOSITY: Not Available

9.2 OTHER INFORMATION:

No additional information available at this time.

SECTION 10. STABILITY and REACTIVITY

10.1 REACTIVITY:

No specific test data related to reactivity available for this product or its ingredients.

10.2 STABILITY:

Stable under conditions of normal storage and use.

10.3 POSSIBILITY OF HAZARDOUS REACTIONS:

Under normal conditions of storage and use, hazardous reactions will not occur.

10.4 CONDITIONS TO AVOID:

Contact with incompatible materials and ignition sources.

10.5 MATERIALS WITH WHICH SUBSTANCE IS INCOMPATIBLE:

Strong oxidizers.

10.6 HAZARDOUS DECOMPOSITION PRODUCTS:

When heated to decomposition this product produces Oxides of carbon (COx), Oxides of sulfur and Hydrocarbons.

SECTION 11. TOXICOLOGICAL INFORMATION

11.1 INFORMATION ON TOXICOLOGICAL EFFECTS:

TOXICITY DATA:

CAS# 64742-53-6

No LD50 Data Available

CAS# 64742-46-4

No LD50 Data Available

CAS# 71-36-3:

Draize test, rabbit, eye: 2 mg Severe;

Draize test, rabbit, eye: 2 mg/24H Severe;

Draize test, rabbit, skin: 405 mg/24H Moderate;

Draize test, rabbit, skin: 20 mg/24H Moderate;

Inhalation, rat: LC50 = 8000 ppm/4H;

Inhalation, rat: LC50 = 24000 mg/m³/4H;

Oral, mouse: LD50 = 100 mg/kg;

Oral, rabbit: LD50 = 3484 mg/kg;

Oral, rabbit: LD50 = 3400 mg/kg;

Oral, rat: LD50 = 790 mg/kg;

Oral, rat: LD50 = 800 mg/kg;

Skin, rabbit: LD50 = 3400 mg/kg;

Acute toxicity	Acute Oral Toxicity Category 4 (Oral)
Skin corrosion / irritation	Skin Irritation Category 2
Serious eye damage / irritation	Eye Damage Category 1
Respiratory or skin sensitization	Based on available data, the classification criteria are not met
Germ cell mutagenicity	Based on available data, the classification criteria are not met
Carcinogenicity	Based on available data, the classification criteria are not met
Reproductive toxicity	Based on available data, the classification criteria are not met
STOT-single exposure	STOT SE Category 3 (Respiratory and Central Nervous Systems)
STOT-repeated exposure	Based on available data, the classification criteria are not met
Aspiration hazard	Based on available data, the classification criteria are not met

ROUTE OF EXPOSURE: The most significant routes of overexposure for this product are by contact with skin, eyes and respiratory system.

ACUTE:

INHALATION: Inhalation of vapor or mist may cause irritation, drowsiness or dizziness

EYE CONTACT: Direct eye contact can cause eye damage, irritation with redness, tearing and blurred vision.

SKIN CONTACT: May cause skin burns or irritation.

INGESTION: Can cause gastrointestinal irritation.

CHRONIC: Prolonged or repeated contact with product and poor hygiene conditions may result in dryness, dermatitis, erythema, oil acne, cracking and defatting of the skin.

SAFETY DATA SHEET

ProtectOLube 4000

TARGET ORGANS: **Acute:** Skin, Respiratory System **Chronic:** Skin

SUSPECTED CANCER AGENT: None of the ingredients are found on the following lists: FEDERAL OSHA Z LIST, NTP, CAL/OSHA, IARC and therefore is not considered to be, nor suspected to be a cancer-causing agent by these agencies.

Note: The severely hydrotreated petroleum ingredients are not considered a potential carcinogen based on IP346 DMSO of less than 3.0 wt%.

REPRODUCTIVE TOXICITY INFORMATION: No specific information is available concerning the effects of this product and its components on the human reproductive system.

SECTION 12. ECOLOGICAL INFORMATION

12.1 TOXICITY:

No specific data available on this product.

12.2 PERSISTENCE AND DEGRADABILITY:

No specific data available on this product.

12.3 BIOACCUMULATIVE POTENTIAL:

No specific data available on this product.

12.4 MOBILITY IN SOIL:

No specific data available on this product.

12.5 RESULTS OF PBT AND vPvB ASSESSMENT:

No specific data available on this product.

12.6 OTHER ADVERSE EFFECTS:

If applied to leaves, this product may kill grasses and small plants by interfering with transpiration and respiration. This product is not toxic to fish but may coat gill structures resulting in suffocation if spilled in shallow, running water. Product may be moderately toxic to amphibians by preventing dermal respiration. This product may cause gastrointestinal distress in birds and mammals through ingestion during pelage grooming.

12.7 WATER ENDANGERMENT CLASS:

May be water endangering in accordance with EU Guideline 91/155-EWG. Do not allow product to reach ground water, water course or sewage system. At present there are no ecotoxicological assessments for this product.

SECTION 13. DISPOSAL CONSIDERATIONS

13.1 WASTE TREATMENT METHODS:

Waste disposal must be in accordance with appropriate U.S. Federal, State, and local regulations, those of Canada, Australia, EU Member States and Japan.

13.2 EU WASTE CODE:

Not determined

SECTION 14. TRANSPORTATION INFORMATION

US DOT, IATA, IMO, ADR:

14.1 U.S. DEPARTMENT OF TRANSPORTATION (DOT) SHIPPING REGULATIONS: This product is classified (per 49 CFR 172.101) by the U.S. Department of Transportation, as follows.

UN IDENTIFICATION NUMBER:

UN1950

PROPER SHIPPING NAME:

Aerosols, flammable (Petroleum gases, liquefied, sweetened)

HAZARD CLASS NUMBER and DESCRIPTION:

2.1 Flammable Gas

PACKING GROUP:

Not applicable

DOT LABEL(S) REQUIRED:

Class 2.1 Flammable Gas

NORTH AMERICAN EMERGENCY RESPONSE GUIDEBOOK NUMBER: 126

RQ QUANTITY:

None

MARINE POLLUTANT: The components of this product are not designated by the Department of Transportation to be Marine Pollutants (49 CFR 172.101, Appendix B).

INTERNATIONAL AIR TRANSPORT ASSOCIATION SHIPPING INFORMATION (IATA): This product is considered as dangerous goods.

INTERNATIONAL MARITIME ORGANIZATION SHIPPING INFORMATION (IMO): This product is considered as dangerous goods.

EUROPEAN AGREEMENT CONCERNING THE INTERNATIONAL CARRIAGE OF DANGEROUS GOODS BY ROAD (ADR): This product is considered by the United Nations Economic Commission for Europe to be dangerous goods.

SAFETY DATA SHEET

ProtectOLube 4000

SECTION 15. REGULATORY INFORMATION

15.1 SAFETY, HEALTH AND ENVIRONMENTAL REGULATIONS SPECIFIC FOR THE SUBSTANCE OR MIXTURE:

UNITED STATES REGULATIONS:

U.S. SARA REPORTING REQUIREMENTS: The components of this product are subject to the reporting requirements of Sections 302, 304, and 313 of Title III of the Superfund Amendments and Reauthorization Act.

This material contains n-Butyl alcohol (CAS# 71-36-3, < 15%), which is subject to the reporting requirements of Section 313 of SARA Title III and 40 CFR Part 373.

U.S. SARA 311/312: Acute Health

U.S. SARA THRESHOLD PLANNING QUANTITY: There are no specific Threshold Planning Quantities for the components of this product. The default Federal SDS submission and inventory requirement filing threshold of 10,000 lbs (4,540 kg) therefore applies, per 40 CFR 370.20.

U.S. CERCLA REPORTABLE QUANTITY (RQ): CAS# 71-36-3: 5000 lb final RQ; 2270 kg final RQ

U.S. TSCA INVENTORY STATUS: The components of this product are listed on the TSCA Inventory or are exempted from listing.

OTHER U.S. FEDERAL REGULATIONS: None known

CALIFORNIA SAFE DRINKING WATER AND TOXIC ENFORCEMENT ACT (PROPOSITION 65): This product does not contain ingredients on the Proposition 65 Lists.

15.2 CANADIAN REGULATIONS:

CANADIAN DSL/NDSL INVENTORY STATUS: Components are DSL Listed, NDSL Listed and/or are exempt from listing

OTHER CANADIAN REGULATIONS: Not applicable.

CANADIAN ENVIRONMENTAL PROTECTION ACT (CEPA) PRIORITIES SUBSTANCES LISTS:

This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations and the SDS contains all of the information required by those regulations.

CANADIAN WHMIS CLASSIFICATION and SYMBOLS: This product has been classified per WHMIS 2015.

15.3 EUROPEAN ECONOMIC COMMUNITY INFORMATION:

This product does meet the definition of a hazardous substance or preparation as defined by the European Union Council Directives 67/548/EEC, 1999/45/EC, 1272/2008/EC and subsequent Directives.

See Section 2 for Details

CHEMICAL SAFETY ASSESSMENT :

No Chemical Safety Assessment has been carried out for this substance/mixture by the supplier.

15.4 AUSTRALIAN INFORMATION FOR PRODUCT:

Components of this product are not listed on the International Chemical Inventory list.

15.5 JAPANESE INFORMATION FOR PRODUCT:

JAPANESE MINISTER OF INTERNATIONAL TRADE AND INDUSTRY (MITI) STATUS: The components of this product are not listed as Class I Specified Chemical Substances, Class II Specified Chemical Substances, or Designated Chemical Substances by the Japanese MITI.

15.6 INTERNATIONAL CHEMICAL INVENTORIES:

Listing of the components on individual country Chemical Inventories is as follows:

Asia-Pac: Not determined.

Australian Inventory of Chemical Substances (AICS): Not determined.

Korean Existing Chemicals List (ECL): Not determined.

Japanese Existing National Inventory of Chemical Substances (ENCS): Not determined.

Philippines Inventory of Chemicals and Chemical Substances (PICCS): Not determined.

Swiss Giftlist of Toxic Substances: Not determined.

U.S. TSCA: Not determined.

SECTION 16. OTHER INFORMATION

PREPARED BY: Chris Eigbrett/
Matt Moore

MSDS to GHS Compliance www.MSDStoGHS.com/
Primrose Oil Company, Inc.

The information contained herein is believed to be accurate but is not warranted to be so. Data and calculations are based on information furnished by the manufacturer of the product and manufacturers of the components of the product. Users are advised to confirm in advance of the need that information is current, applicable and suited to the circumstances of use. Primrose Oil Company, Inc. assumes no responsibility for injury to vendee or third party person proximately caused by the material if reasonable safety procedures are not adhered to as stipulated in the data sheet. Furthermore, Primrose Oil Company, Inc. assumes no responsibility for injury caused by abnormal use of this material even if reasonable safety procedures are followed.

END OF SDS SHEET