# Amor Plate with Moly-D EP Open Gear Lubricant

Prepared according to U.S. OSHA, CMA, ANSI, Canadian WHMIS regulations

## **SECTION 1 - PRODUCT AND COMPANY IDENTIFICATION**

PRODUCT NAME: Amor Plate with Moly-D EP Open Gear Lubricant

PRODUCT NUMBER: 55

PRODUCT DESCRIPTION: Open Gear Lubricant

U.N. NUMBER: None

U.N. DANGEROUS GOODS CLASS: Non-Regulated Material

SUPPLIER/MANUFACTURER'S NAME: Primrose Oil Company, Inc.

ADDRESS: 11444 Denton Drive, P.O. Box 29665, Dallas, Texas 75229 USA

EMERGENCY PHONE: 1-800-633-8253 (For Emergencies Only)
BUSINESS PHONE: 1-972-241-1100 (For product information)

WEB SITE: <a href="https://www.primrose.com">www.primrose.com</a>
DATE OF PREPARATION: September 13, 2017

DATE OF LAST REVISION: November 20, 2013, September 16, 2025

## **SECTION 2 - HAZARDS IDENTIFICATION**

#### **EMERGENCY OVERVIEW:**

This product is a light brown to brown colored liquid with a mild petroleum odor.

**HEALTH HAZARDS:** Repeated or prolonged contact with skin may cause irritation. Contact with eyes can cause irritation.

**FLAMMABILITY:** This product is a Non-Flammable product with a flash point >200°F.

**ENVIRONMENTAL EFFECTS:** The Environmental effects of this product have not been investigated, however this

product contains ingredients that may cause adverse effects to aquatic life.

US DOT SYMBOLS CANADA (WHMIS) SYMBOLS GHS HAZARD SYMBOL(S)

Non-Regulated Complies with WHMIS 2015



Signal Word: Warning!

# **COMPONENTS DETERMINING HAZARDS:**

Polybutene, 5,5'-dithiodi-1,3,4-thiadiazole-2(3H)-thione, Silane, dichlorodimethyl-, reaction products with silica, Molybdenum, bis(dibutylcarbamodithioato)di-mu-oxodioxodi-, sulfurized

# GHS HAZARD CLASSIFICATION(S):

Skin Irritation Category 2 Eye Irritation Category 2A

### **HAZARD STATEMENTS:**

Causes skin irritation Causes eye irritation

## **PREVENTION STATEMENTS:**

Wash thoroughly after handling

Wear protective gloves / eye protection

# **RESPONSE STATEMENTS:**

IF ON SKIN: Wash with plenty of water.

Specific treatment (See Section 4 of this SDS).

If skin irritation occurs: Get medical advice/attention.

Take off contaminated clothing and wash it before reuse.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

If eye irritation persists: Get medical advice/attention.

## **STORAGE STATEMENTS:**

None applicable.

# **DISPOSAL STATEMENTS:**

Not applicable.

# Amor Plate with Moly-D EP Open Gear Lubricant

## **HEALTH HAZARDS OR RISKS FROM EXPOSURE:**

ACUTE:

**INHALATION:** Not expected to cause respiratory hazards at ambient temperatures.

**EYE CONTACT:** Direct eye contact can cause irritation with redness, tearing and blurred vision.

**SKIN CONTACT:** May cause skin irritation.

**INGESTION:** Ingestion of this product can cause a laxative effect. May be an aspiration hazard.

CHRONIC: Prolonged or repeated contact with product and poor hygiene conditions may result in skin dryness or

dermatitis.

TARGET ORGANS: ACUTE: Eye, Skin CHRONIC: Skin

# **SECTION 3 - COMPOSITION and INFORMATION ON INGREDIENTS**

**HAZARDS DISCLOSURE:** This product does contain known hazardous materials in reportable levels as defined by the OSHA Hazard Communication Standard 29 CFR 1910.1200. As defined under Sara 311 and 312, this product contains known hazardous materials.

HAZARDOUS INGREDIENTS:	CAS#	WT %	HAZARD CLASSIFICATION	
Distillates (petroleum), solvent-dewaxed heavy paraffinic	64742-65-0	80 – 90%	NOT CLASSFIED (*NOTE - <3% DMSO)	
Polybutene	9003-29-6	30 – 35%	SKIN IRRIT CAT 2, EYE IRRIT CAT 2A	
5,5'-dithiodi-1,3,4-thiadiazole-2(3H)-thione	72676-55-2	5 – 15%	SKIN IRRIT CAT 2, EYE IRRIT CAT 2A	
Silane, dichlorodimethyl-, reaction products with silica	68611-44-9	1 – 10%	SKIN IRRIT CAT 2, EYE IRRIT CAT 2A	
Molybdenum, bis(dibutylcarbamodithioato)di-mu- oxodioxodi-, sulfurized	68412-26-0	1 – 5%	SKIN IRRIT CAT 2, EYE IRRIT CAT 2A	

Each of the other components present are less than 1 percent concentration (0.1% concentration for potential carcinogens, reproductive toxins, respiratory tract sensitizers, and mutagens)

# **SECTION 4 - FIRST-AID MEASURES**

Contaminated individuals of chemical exposure must be taken for medical attention if any adverse effect occurs. Rescuers should be taken for medical attention, if necessary. Take copy of label and MSDS to health professional with contaminated individual.

**EYE CONTACT:** If product enters the eyes, open eyes while under gentle running water for at least 15 minutes. Seek medical attention if irritation or blurred vision continues.

SKIN CONTACT: Wash skin thoroughly after handling. Seek medical attention if irritation develops and persists.

**INHALATION:** If breathing becomes difficult, remove victim to fresh air. If necessary, use artificial respiration to support vital functions. Seek medical attention immediately.

**INGESTION:** If product is swallowed, call physician or poison control center for most current information. If professional advice is not available, do not induce vomiting. Never induce vomiting or give diluents (milk or water) to someone who is unconscious, having convulsions, or who cannot swallow. Seek medical advice. Take a copy of the label and/or MSDS with the victim to the health professional.

**MEDICAL CONDITIONS AGGRAVATED BY EXPOSURE:** Individuals with pre-existing skin disorders or respiratory conditions should avoid contact with this product.

**RECOMMENDATIONS TO PHYSICIANS:** Treat symptoms and reduce over-exposure.

# SECTION 5 - FIRE-FIGHTING MEASURES

FLASH POINT: >200°F
AUTOIGNITION TEMPERATURE: Not Established

FLAMMABLE LIMITS (in air by volume, %): Lower (LEL): Not Established Upper (UEL): Not Established Dry chemical, carbon dioxide, foam. Do not use forced stream as

this could cause fire to spread.

UNUSUAL FIRE AND EXPLOSION HAZARDS:

Explosion Sensitivity to Mechanical Impact:

Explosion Sensitivity to Static Discharge:

Not Sensitive

Not Sensitive

# Amor Plate with Moly-D EP Open Gear Lubricant

SPECIAL FIRE-FIGHTING PROCEDURES: NFPA Rating System



Incipient fire responders should wear eye protection. Structural firefighters must wear Self-Contained Breathing Apparatus and full protective equipment. Isolate materials not yet involved in the fire and protect personnel. Move containers from fire area if this can be done without risk; otherwise, cool with carefully applied water spray. If possible, prevent runoff water from entering storm drains, bodies of water, or other environmentally sensitive areas.

# **SECTION 6 - ACCIDENTAL RELEASE MEASURES**

**SPILL AND LEAK RESPONSE:** Personnel should be trained for spill response operations. Contain and recover if possible. Use non-sparking tools and equipment. Cover spilled product with sand, earth or other non-combustible absorbent material. Pickup spilled material immediately and place in appropriate containers. Dispose of in accordance with applicable Federal, State, and local procedures (see Section 13, Disposal Considerations).

Do not discharge to sewers and surface waters. Notify authorities if entry occurs.

U.S. Regulations (CERCLA) requires reporting spills and releases to soil, water and air in excess of reportable quantities. The toll free number for the US Coast Guard National Response Center is (800) 424-8802.

# **SECTION 7 - HANDLING and STORAGE**

**WORK PRACTICES AND HYGIENE PRACTICES:** As with all chemicals, avoid getting this product on you. Wash thoroughly after handling this product. Use in a well-ventilated location.

**STORAGE AND HANDLING PRACTICES:** Store containers in a cool, dry location. Keep away from sources of ignition. Keep container tightly closed when not in use. Protect from physical damage.

# **SECTION 8 - EXPOSURE CONTROLS - PERSONAL PROTECTION**

### **EXPOSURE LIMITS/GUIDELINES:**

Chemical Name	CAS#	ACGIH TWA	OSHA TWA
Severely Solvent Refined Heavy Paraffinic Petroleum Oil	64742-65-0	5 mg/m³ Oil Mist	5 mg/m³ Oil Mist
Polybutene	9003-29-6	Not Listed	Not Listed
5,5'-dithiodi-1,3,4-thiadiazole-2(3H)-thione	72676-55-2	Not Listed	Not Listed
Silane, dichlorodimethyl-, reaction products with silica	68611-44-9	Not Listed	Not Listed
Molybdenum, bis(dibutylcarbamodithioato)di-mu- oxodioxodi-, sulfurized	68412-26-0	Not Listed	Not Listed

Currently, International exposure limits are not established for all the components of this product. Please check with competent authority in each country for the most recent limits in place.

**VENTILATION AND ENGINEERING CONTROLS:** Use with adequate ventilation to ensure exposure levels are maintained below the limits provided above. Use local exhaust ventilation to control airborne vapors.

The following information on appropriate Personal Protective Equipment is provided to assist employers in complying with OSHA regulations found in 29 CFR Subpart I (beginning at 1910.132) or equivalent standard of Canada. Please reference applicable regulations and standards for relevant details.

**RESPIRATORY PROTECTION:** Not normally required when using this product. Maintain airborne contaminant concentrations below guidelines listed above, if applicable. If necessary, use only respiratory protection authorized in the U.S. Federal OSHA Respiratory Protection Standard (29 CFR 1910.134), equivalent U.S. State standards, Canadian CSA Standard Z94.4-93.

**EYE PROTECTION:** Wear safety glasses or chemical goggles as appropriate were splashing is possible. If necessary, refer to U.S. OSHA 29 CFR 1910.133 or appropriate Canadian Standards.

**HAND PROTECTION:** Wear chemical resistant gloves as appropriate to prevent skin contact. If necessary, refer to U.S. OSHA 29 CFR 1910.138 or appropriate Standards of Canada.

**BODY PROTECTION:** Use body protection appropriate to prevent skin contact (e.g. lab coat, overalls). If necessary, refer to appropriate Standards of Canada, or appropriate Standards of the EU, Australian Standards, or relevant Japanese Standards.

# Amor Plate with Moly-D EP Open Gear Lubricant

# **SECTION 9 - PHYSICAL and CHEMICAL PROPERTIES**

PHYSICAL STATE: Liquid

APPEARANCE & ODOR: green colored liquid with a mild petroleum odor

Mild

ODOR THRESHOLD (PPM):

VAPOR PRESSURE (mmHg):

VAPOR DENSITY (AIR=1):

EVAPORATION RATE (nBuAc = 1):

BOILING POINT (C°):

Not Available

Not Available

Not Available

Not Available

nH·

SPECIFIC GRAVITY 20°C: (WATER =1)

SOLUBILITY IN WATER (%)

VOC:

0.9

Partial

Not Available

# **SECTION 10 - STABILITY and REACTIVITY**

**STABILITY:** Product is stable

**DECOMPOSITION PRODUCTS:** When heated to decomposition this product produces oxides of carbon and nitrogen

including CO and CO2, and some metallic oxides.

MATERIALS WITH WHICH SUBSTANCE IS INCOMPATIBLE: Strong oxidizers.

**HAZARDOUS POLYMERIZATION:** Will not occur.

**CONDITIONS TO AVOID:** Contact with incompatible materials and ignition sources

# **SECTION 11 - TOXICOLOGICAL INFORMATION**

**TOXICITY DATA:** No specific data available for this product.

**SUSPECTED CANCER AGENT:** One or more of the ingredients are found on the following lists: FEDERAL OSHA Z LIST, NTP, CAL/OSHA, IARC and therefore is considered to be, or suspected to be a cancer-causing agent by these agencies.

**Note:** This product contains petroleum products which are severely refined and not considered a potential carcinogen based on IP346 DMSO of less than 3.0 wt%.

**IRRITANCY OF PRODUCT:** Contact with this product can be irritating to skin and eyes.

**SENSITIZATION OF PRODUCT:** Ingredients in this product are not considered a sensitizer.

REPRODUCTIVE TOXICITY INFORMATION: No information available

### SECTION 12 - ECOLOGICAL INFORMATION

# ALL WORK PRACTICES MUST BE AIMED AT ELIMINATING ENVIRONMENTAL CONTAMINATION.

**ENVIRONMENTAL STABILITY:** No specific data is available for this product; however this product is not expected to be readily biodegradable

**EFFECT OF MATERIAL ON PLANTS or ANIMALS:** If applied to leaves, this product may kill grasses and small plants by interfering with transpiration and respiration. This product is not toxic to fish but may coat gill structures resulting in suffocation if spilled in shallow, running water. Product may be moderately toxic to amphibians by preventing dermal respiration. This product may cause gastrointestinal distress in birds and mammals through ingestion during pelage grooming.

**EFFECT OF CHEMICAL ON AQUATIC LIFE:** No evidence is currently available on this product's effects on aquatic life. This product does contain ingredients that are considered hazardous to aquatic organisms.

# **SECTION 13 - DISPOSAL CONSIDERATIONS**

**PREPARING WASTES FOR DISPOSAL:** Waste disposal must be in accordance with appropriate Federal, State, and local regulations, those of Canada, Australia, EU Member States and Japan.

September 2025 Page 4 of 6 Rev 3

Amor Plate with Moly-D EP Open Gear Lubricant

## **SECTION 14 - TRANSPORTATION INFORMATION**

#### US DOT; IATA; IMO; ADR:

THIS PRODUCT IS NOT HAZARDOUS AS DEFINED BY 49 CFR 172.101 BY THE U.S. DEPARTMENT OF TRANSPORTATION.

PROPER SHIPPING NAME: Non-Regulated Material HAZARD CLASS NUMBER and DESCRIPTION: None

**UN IDENTIFICATION NUMBER: None** 

**PACKING GROUP: None** 

DOT LABEL(S) REQUIRED: None

NORTH AMERICAN EMERGENCY RESPONSE GUIDEBOOK NUMBER (2004): None

MARINE POLLUTANT: None of the ingredients are classified by the DOT as a Marine Pollutant (as defined by 49

CFR 172.101, Appendix B)

U.S. DEPARTMENT OF TRANSPORTATION (DOT) SHIPPING REGULATIONS:

This product is not classified as dangerous goods, per U.S. DOT regulations, under 49 CFR 172.101.

TRANSPORT CANADA, TRANSPORTATION OF DANGEROUS GOODS REGULATIONS:

This product is not classified as Dangerous Goods, per regulations of Transport Canada.

INTERNATIONAL AIR TRANSPORT ASSOCIATION (IATA):

This product is not classified as Dangerous Goods, by rules of IATA:

INTERNATIONAL MARITIME ORGANIZATION (IMO) DESIGNATION:

This product is not classified as Dangerous Goods by the International Maritime Organization.

# **SECTION 15 - REGULATORY INFORMATION**

# **UNITED STATES REGULATIONS**

**SARA REPORTING REQUIREMENTS:** This product is subject to the reporting requirements of Sections 302, 304 and 313 of Title III of the Superfund Amendments and Reauthorization Act., as follows: None

TSCA: All components in this product are listed on the US Toxic Substances Control Act (TSCA) inventory of chemicals.

### SARA 311/312:

Acute Health: Yes Chronic Health: No Fire: No Reactivity: No

<u>U.S. SARA THRESHOLD PLANNING QUANTITY:</u> There are no specific Threshold Planning Quantities for this product. The default Federal MSDS submission and inventory requirement filing threshold of 10,000 lb (4,540 kg) may apply, per 40 CFR 370.20.

U.S. CERCLA REPORTABLE QUANTITY (RQ): None

<u>CALIFORNIA SAFE DRINKING WATER AND TOXIC ENFORCEMENT ACT (PROPOSITION 65)</u>: This product does not contain ingredients that are on the California Proposition 65 lists.

### **CANADIAN REGULATIONS:**

U.S. TSCA:

CANADIAN DSL/NDSL INVENTORY STATUS: All of the components of this product are on the DSL Inventory

**CANADIAN ENVIRONMENTAL PROTECTION ACT (CEPA) PRIORITIES SUBSTANCES LISTS:** No component of this product is on the CEPA First Priorities Substance Lists.

Listed

CANADIAN WHMIS CLASSIFICATION and SYMBOLS: Complies with WHMIS 2015.

### **INTERNATIONAL CHEMICAL INVENTORIES:**

Listing of the components on individual country Chemical Inventories is as follows:

Asia-Pac:

Australian Inventory of Chemical Substances (AICS):

Korean Existing Chemicals List (ECL):

Japanese Existing National Inventory of Chemical Substances (ENCS):

Philippines Inventory if Chemicals and Chemical Substances (PICCS):

Swiss Giftliste List of Toxic Substances:

Listed or Exempt

# Amor Plate with Moly-D EP Open Gear Lubricant

## **SECTION 16 - OTHER INFORMATION**

PREPARED BY: Chris Eigbrett/ MSDS to GHS Compliance/ Primrose Oil Company, Inc.

#### Disclaimer:

This information is furnished without warranty, expressed or implied, except that it is accurate to the best knowledge of Primrose Oil Company, Inc. The data on this sheet is related only to the specific material designated herein. Primrose Oil Company, Inc. assumes no legal responsibility for use or reliance upon this data.

To the best of our knowledge, the information contained herein is accurate. However, neither the above named supplier nor any of its subsidiaries assumes any liability whatsoever for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.

#### **Product Notes:**

The Petroleum Oils are considered a carcinogen on the international data base. Because they are all severely hydrotreated they are not considered a potential carcinogen based on IP346 DMSO of less than 3.0 wt%.

#### **Revision Levels:**

November 20, 2013 – New September 13, 2017 – Updated GHS elements

September 2025 Page 6 of 6 Rev 3