

238 | Odyssey[®] 1800

Synthetic Moly Motor Oil API SP, SAE 0W-20

DESCRIPTION:

Odyssey 1800 is a high performance, synthetic moly motor oil. Odyssey 1800 gives multigrade performance for all seasons and all temperatures. It meets SP API performance standards for gasoline engines, and encompasses all the core product features in Odyssey® engine oils. Odyssey 1800 is highly formulated for superior performance with extended drain intervals.

COMPOSITION:

Odyssey 1800 begins with its special synthetic base stock which consists of synthetic base stocks and polymers which are refined to an exceptionally high viscosity index. Odyssey 1800 is fully compatible with most other synthetic and conventional mineral oil based motor oils.

Odyssey 1800 is formulated as an extended drain motor oil with its superior additive package. Extensive performance testing has proven exceptional deposit control, thermal stability and elimination of most wear, making much longer drain intervals possible. Highly efficient detergent alkalinity provides super engine cleanliness and spells a dramatic reduction in total maintenance. The superior oxidation and thermal stability of Odyssey 1800, with its highly shear stable viscosity index improvers, prevents oil breakdown, making much longer drain intervals possible. Dramatically reduced oil consumption and increased fuel economy can also be attributed to the use of this high performance product. Outstanding low temperature flow allows for easy starts. Plus, it provides for high temperature protection, and low speed pre-ignition (LSPI) protection. Wear is essentially eliminated with the addition of our exclusive oil soluble friction modifier, Moly-D®.

PERFORMANCE CHARACTERISTICS:

Meets and exceeds the following performance categories and specifications:

API SP ILSAC GF-6A Chrysler – MS6395 GM 6094M GM 4718M Ford WSS-M2C961-A1 Ford WSS-M2C946-A Ford WSS 913-A/B/C/D

USES:

Odyssey 1800 is recommended for use in gasoline engines.

APPLICATIONS:

- Passenger Cars
- 4-Cycle Marine Engines
- Trucks
- Recreational Engines



238

Odyssey® 1800 Synthetic Moly Motor Oil, API SP, SAE 0W-20

TYPICAL SPECIFICATIONS:

Product No.	238
SAE Grade	0W-20
Viscosity,	
cSt @ 100°C	8.5
Viscosity Index	140
Flash Point, °F	> 390
API Gravity	36
Sulfated Ash, % wt	≤0.9
Base Number (BN)	7